



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	-10	-9	-8	-7	-6	-5	-4	-3	-2	-1	0	°F
-450							-4.345	-4.345	-4.345	-4.344	-4.344	-450
-440	-4.344	-4.344	-4.343	-4.343	-4.342	-4.342	-4.341	-4.341	-4.340	-4.340	-4.339	-440
-430	-4.339	-4.338	-4.337	-4.337	-4.336	-4.335	-4.334	-4.333	-4.332	-4.331	-4.330	-430
-420	-4.330	-4.329	-4.327	-4.326	-4.325	-4.324	-4.322	-4.321	-4.319	-4.318	-4.316	-420
-410	-4.316	-4.315	-4.313	-4.312	-4.310	-4.308	-4.306	-4.305	-4.303	-4.301	-4.299	-410
-400	-4.299	-4.297	-4.295	-4.293	-4.291	-4.288	-4.286	-4.284	-4.282	-4.279	-4.277	-400
-390	-4.277	-4.275	-4.272	-4.270	-4.267	-4.264	-4.262	-4.259	-4.256	-4.254	-4.251	-390
-380	-4.251	-4.248	-4.245	-4.242	-4.239	-4.236	-4.233	-4.230	-4.226	-4.223	-4.220	-380
-370	-4.220	-4.217	-4.213	-4.210	-4.206	-4.203	-4.199	-4.196	-4.192	-4.189	-4.185	-370
-360	-4.185	-4.181	-4.177	-4.174	-4.170	-4.166	-4.162	-4.158	-4.154	-4.150	-4.145	-360
-350	-4.145	-4.141	-4.137	-4.133	-4.128	-4.124	-4.120	-4.115	-4.111	-4.106	-4.102	-350
-340	-4.102	-4.097	-4.092	-4.088	-4.083	-4.078	-4.073	-4.068	-4.064	-4.059	-4.054	-340
-330	-4.054	-4.049	-4.043	-4.038	-4.033	-4.028	-4.023	-4.017	-4.012	-4.007	-4.001	-330
-320	-4.001	-3.996	-3.990	-3.985	-3.979	-3.974	-3.968	-3.962	-3.957	-3.951	-3.945	-320
-310	-3.945	-3.939	-3.933	-3.927	-3.921	-3.915	-3.909	-3.903	-3.897	-3.891	-3.884	-310
-300	-3.884	-3.878	-3.872	-3.866	-3.859	-3.853	-3.846	-3.840	-3.833	-3.827	-3.820	-300
-290	-3.820	-3.813	-3.807	-3.800	-3.793	-3.786	-3.779	-3.773	-3.766	-3.759	-3.752	-290
-280	-3.752	-3.745	-3.738	-3.730	-3.723	-3.716	-3.709	-3.702	-3.694	-3.687	-3.679	-280
-270	-3.679	-3.672	-3.665	-3.657	-3.650	-3.642	-3.634	-3.627	-3.619	-3.611	-3.604	-270
-260	-3.604	-3.596	-3.588	-3.580	-3.572	-3.564	-3.556	-3.548	-3.540	-3.532	-3.524	-260
-250	-3.524	-3.516	-3.508	-3.499	-3.491	-3.483	-3.474	-3.466	-3.458	-3.449	-3.441	-250
-240	-3.441	-3.432	-3.424	-3.415	-3.407	-3.398	-3.389	-3.380	-3.372	-3.363	-3.354	-240
-230	-3.354	-3.345	-3.336	-3.327	-3.318	-3.309	-3.300	-3.291	-3.282	-3.273	-3.264	-230
-220	-3.264	-3.255	-3.246	-3.236	-3.227	-3.218	-3.208	-3.199	-3.189	-3.180	-3.171	-220
-210	-3.171	-3.161	-3.151	-3.142	-3.132	-3.123	-3.113	-3.103	-3.093	-3.084	-3.074	-210
-200	-3.074	-3.064	-3.054	-3.044	-3.034	-3.024	-3.014	-3.004	-2.994	-2.984	-2.974	-200
-190	-2.974	-2.964	-2.954	-2.943	-2.933	-2.923	-2.912	-2.902	-2.892	-2.881	-2.871	-190
-180	-2.871	-2.860	-2.850	-2.839	-2.829	-2.818	-2.808	-2.797	-2.786	-2.776	-2.765	-180
-170	-2.765	-2.754	-2.743	-2.733	-2.722	-2.711	-2.700	-2.689	-2.678	-2.667	-2.656	-170
-160	-2.656	-2.645	-2.634	-2.623	-2.612	-2.601	-2.589	-2.578	-2.567	-2.556	-2.544	-160
-150	-2.544	-2.533	-2.522	-2.510	-2.499	-2.488	-2.476	-2.465	-2.453	-2.442	-2.430	-150



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	-10	-9	-8	-7	-6	-5	-4	-3	-2	-1	0	°F
-140	-2.430	-2.418	-2.407	-2.395	-2.384	-2.372	-2.360	-2.348	-2.337	-2.325	-2.313	-140
-130	-2.313	-2.301	-2.289	-2.277	-2.265	-2.254	-2.242	-2.230	-2.218	-2.206	-2.193	-130
-120	-2.193	-2.181	-2.169	-2.157	-2.145	-2.133	-2.121	-2.108	-2.096	-2.084	-2.072	-120
-110	-2.072	-2.059	-2.047	-2.035	-2.022	-2.010	-1.997	-1.985	-1.972	-1.960	-1.947	-110
-100	-1.947	-1.935	-1.922	-1.910	-1.897	-1.884	-1.872	-1.859	-1.846	-1.834	-1.821	-100
-90	-1.821	-1.808	-1.795	-1.783	-1.770	-1.757	-1.744	-1.731	-1.718	-1.705	-1.692	-90
-80	-1.692	-1.679	-1.666	-1.653	-1.640	-1.627	-1.614	-1.601	-1.588	-1.575	-1.562	-80
-70	-1.562	-1.549	-1.536	-1.522	-1.509	-1.496	-1.483	-1.470	-1.456	-1.443	-1.430	-70
-60	-1.430	-1.416	-1.403	-1.390	-1.376	-1.363	-1.349	-1.336	-1.323	-1.309	-1.296	-60
-50	-1.296	-1.282	-1.269	-1.255	-1.242	-1.228	-1.214	-1.201	-1.187	-1.174	-1.160	-50
-40	-1.160	-1.146	-1.133	-1.119	-1.105	-1.092	-1.078	-1.064	-1.050	-1.037	-1.023	-40
-30	-1.023	-1.009	-0.995	-0.981	-0.967	-0.954	-0.940	-0.926	-0.912	-0.898	-0.884	-30
-20	-0.884	-0.870	-0.856	-0.842	-0.828	-0.814	-0.800	-0.786	-0.772	-0.758	-0.744	-20
-10	-0.744	-0.730	-0.716	-0.702	-0.688	-0.674	-0.660	-0.646	-0.632	-0.617	-0.603	-10
0	-0.603	-0.589	-0.575	-0.561	-0.546	-0.532	-0.518	-0.504	-0.490	-0.475	-0.461	0
°F	-10	-9	-8	-7	-6	-5	-4	-3	-2	-1	0	°F
°F	0	1	2	3	4	5	6	7	8	9	10	°F
0	-0.461	-0.447	-0.433	-0.418	-0.404	-0.390	-0.375	-0.361	-0.347	-0.332	-0.318	0
10	-0.318	-0.304	-0.289	-0.275	-0.260	-0.246	-0.232	-0.217	-0.203	-0.188	-0.174	10
20	-0.174	-0.159	-0.145	-0.131	-0.116	-0.102	-0.087	-0.073	-0.058	-0.044	-0.029	20
30	-0.029	-0.015	0.000	0.014	0.029	0.043	0.058	0.072	0.087	0.101	0.116	30
40	0.116	0.130	0.145	0.159	0.174	0.188	0.203	0.217	0.232	0.246	0.261	40
50	0.261	0.275	0.290	0.305	0.319	0.334	0.349	0.363	0.378	0.393	0.407	50
60	0.407	0.422	0.437	0.451	0.466	0.481	0.496	0.510	0.525	0.540	0.555	60
70	0.555	0.570	0.584	0.599	0.614	0.629	0.644	0.659	0.674	0.688	0.703	70
80	0.703	0.718	0.733	0.748	0.763	0.778	0.793	0.808	0.823	0.838	0.853	80
90	0.853	0.868	0.883	0.898	0.913	0.928	0.943	0.958	0.974	0.989	1.004	90
100	1.004	1.019	1.034	1.049	1.065	1.080	1.095	1.110	1.125	1.141	1.156	100
110	1.156	1.171	1.186	1.202	1.217	1.232	1.248	1.263	1.278	1.294	1.309	110
120	1.309	1.324	1.340	1.355	1.371	1.386	1.402	1.417	1.432	1.448	1.463	120
130	1.463	1.479	1.494	1.510	1.525	1.541	1.557	1.572	1.588	1.603	1.619	130
140	1.619	1.635	1.650	1.666	1.682	1.697	1.713	1.729	1.744	1.760	1.776	140



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
150	1.776	1.791	1.807	1.823	1.839	1.855	1.870	1.886	1.902	1.918	1.934	150
160	1.934	1.950	1.965	1.981	1.997	2.013	2.029	2.045	2.061	2.077	2.093	160
170	2.093	2.109	2.125	2.141	2.157	2.173	2.189	2.205	2.221	2.237	2.253	170
180	2.253	2.269	2.285	2.301	2.318	2.334	2.350	2.366	2.382	2.398	2.415	180
190	2.415	2.431	2.447	2.463	2.480	2.496	2.512	2.528	2.545	2.561	2.577	190
200	2.577	2.594	2.610	2.626	2.643	2.659	2.676	2.692	2.708	2.725	2.741	200
210	2.741	2.758	2.774	2.791	2.807	2.824	2.840	2.857	2.873	2.890	2.906	210
220	2.906	2.923	2.939	2.956	2.973	2.989	3.006	3.022	3.039	3.056	3.072	220
230	3.072	3.089	3.106	3.123	3.139	3.156	3.173	3.189	3.206	3.223	3.240	230
240	3.240	3.257	3.273	3.290	3.307	3.324	3.341	3.358	3.374	3.391	3.408	240
250	3.408	3.425	3.442	3.459	3.476	3.493	3.510	3.527	3.544	3.561	3.578	250
260	3.578	3.595	3.612	3.629	3.646	3.663	3.680	3.697	3.714	3.731	3.748	260
270	3.748	3.766	3.783	3.800	3.817	3.834	3.851	3.869	3.886	3.903	3.920	270
280	3.920	3.937	3.955	3.972	3.989	4.007	4.024	4.041	4.058	4.076	4.093	280
290	4.093	4.110	4.128	4.145	4.162	4.180	4.197	4.215	4.232	4.250	4.267	290
300	4.267	4.284	4.302	4.319	4.337	4.354	4.372	4.389	4.407	4.424	4.442	300
310	4.442	4.459	4.477	4.495	4.512	4.530	4.547	4.565	4.583	4.600	4.618	310
320	4.618	4.635	4.653	4.671	4.688	4.706	4.724	4.742	4.759	4.777	4.795	320
330	4.795	4.813	4.830	4.848	4.866	4.884	4.901	4.919	4.937	4.955	4.973	330
340	4.973	4.991	5.008	5.026	5.044	5.062	5.080	5.098	5.116	5.134	5.152	340
350	5.152	5.170	5.188	5.206	5.224	5.241	5.259	5.277	5.295	5.314	5.332	350
360	5.332	5.350	5.368	5.386	5.404	5.422	5.440	5.458	5.476	5.494	5.512	360
370	5.512	5.531	5.549	5.567	5.585	5.603	5.621	5.639	5.658	5.676	5.694	370
380	5.694	5.712	5.731	5.749	5.767	5.785	5.804	5.822	5.840	5.858	5.877	380
390	5.877	5.895	5.913	5.932	5.950	5.968	5.987	6.005	6.024	6.042	6.060	390
400	6.060	6.079	6.097	6.116	6.134	6.152	6.171	6.189	6.208	6.226	6.245	400
410	6.245	6.263	6.282	6.300	6.319	6.337	6.356	6.374	6.393	6.411	6.430	410
420	6.430	6.449	6.467	6.486	6.504	6.523	6.542	6.560	6.579	6.597	6.616	420
430	6.616	6.635	6.653	6.672	6.691	6.710	6.728	6.747	6.766	6.784	6.803	430
440	6.803	6.822	6.841	6.859	6.878	6.897	6.916	6.934	6.953	6.972	6.991	440
450	6.991	7.010	7.029	7.047	7.066	7.085	7.104	7.123	7.142	7.161	7.179	450
460	7.179	7.198	7.217	7.236	7.255	7.274	7.293	7.312	7.331	7.350	7.369	460
470	7.369	7.388	7.407	7.426	7.445	7.464	7.483	7.502	7.521	7.540	7.559	470
480	7.559	7.578	7.597	7.616	7.635	7.654	7.673	7.692	7.711	7.731	7.750	480
490	7.750	7.769	7.788	7.807	7.826	7.845	7.865	7.884	7.903	7.922	7.941	490



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
<b>500</b>	7.941	7.960	7.980	7.999	8.018	8.037	8.057	8.076	8.095	8.114	8.134	<b>500</b>
<b>510</b>	8.134	8.153	8.172	8.191	8.211	8.230	8.249	8.269	8.288	8.307	8.327	<b>510</b>
<b>520</b>	8.327	8.346	8.365	8.385	8.404	8.423	8.443	8.462	8.482	8.501	8.520	<b>520</b>
<b>530</b>	8.520	8.540	8.559	8.579	8.598	8.617	8.637	8.656	8.676	8.695	8.715	<b>530</b>
<b>540</b>	8.715	8.734	8.754	8.773	8.793	8.812	8.832	8.851	8.871	8.890	8.910	<b>540</b>
<b>550</b>	8.910	8.929	8.949	8.968	8.988	9.008	9.027	9.047	9.066	9.086	9.105	<b>550</b>
<b>560</b>	9.105	9.125	9.145	9.164	9.184	9.204	9.223	9.243	9.262	9.282	9.302	<b>560</b>
<b>570</b>	9.302	9.321	9.341	9.361	9.381	9.400	9.420	9.440	9.459	9.479	9.499	<b>570</b>
<b>580</b>	9.499	9.519	9.538	9.558	9.578	9.598	9.617	9.637	9.657	9.677	9.696	<b>580</b>
<b>590</b>	9.696	9.716	9.736	9.756	9.776	9.795	9.815	9.835	9.855	9.875	9.895	<b>590</b>
<b>600</b>	9.895	9.914	9.934	9.954	9.974	9.994	10.014	10.034	10.054	10.073	10.093	<b>600</b>
<b>610</b>	10.093	10.113	10.133	10.153	10.173	10.193	10.213	10.233	10.253	10.273	10.293	<b>610</b>
<b>620</b>	10.293	10.313	10.333	10.353	10.373	10.393	10.413	10.433	10.453	10.473	10.493	<b>620</b>
<b>630</b>	10.493	10.513	10.533	10.553	10.573	10.593	10.613	10.633	10.653	10.673	10.693	<b>630</b>
<b>640</b>	10.693	10.713	10.733	10.753	10.774	10.794	10.814	10.834	10.854	10.874	10.894	<b>640</b>
<b>650</b>	10.894	10.914	10.934	10.955	10.975	10.995	11.015	11.035	11.055	11.076	11.096	<b>650</b>
<b>660</b>	11.096	11.116	11.136	11.156	11.177	11.197	11.217	11.237	11.257	11.278	11.298	<b>660</b>
<b>670</b>	11.298	11.318	11.338	11.359	11.379	11.399	11.419	11.440	11.460	11.480	11.501	<b>670</b>
<b>680</b>	11.501	11.521	11.541	11.561	11.582	11.602	11.622	11.643	11.663	11.683	11.704	<b>680</b>
<b>690</b>	11.704	11.724	11.744	11.765	11.785	11.805	11.826	11.846	11.867	11.887	11.907	<b>690</b>
<b>700</b>	11.907	11.928	11.948	11.968	11.989	12.009	12.030	12.050	12.071	12.091	12.111	<b>700</b>
<b>710</b>	12.111	12.132	12.152	12.173	12.193	12.214	12.234	12.255	12.275	12.295	12.316	<b>710</b>
<b>720</b>	12.316	12.336	12.357	12.377	12.398	12.418	12.439	12.459	12.480	12.500	12.521	<b>720</b>
<b>730</b>	12.521	12.542	12.562	12.583	12.603	12.624	12.644	12.665	12.685	12.706	12.726	<b>730</b>
<b>740</b>	12.726	12.747	12.768	12.788	12.809	12.829	12.850	12.871	12.891	12.912	12.932	<b>740</b>
<b>750</b>	12.932	12.953	12.974	12.994	13.015	13.036	13.056	13.077	13.098	13.118	13.139	<b>750</b>
<b>760</b>	13.139	13.159	13.180	13.201	13.221	13.242	13.263	13.284	13.304	13.325	13.346	<b>760</b>
<b>770</b>	13.346	13.366	13.387	13.408	13.428	13.449	13.470	13.491	13.511	13.532	13.553	<b>770</b>
<b>780</b>	13.553	13.574	13.594	13.615	13.636	13.657	13.677	13.698	13.719	13.740	13.760	<b>780</b>
<b>790</b>	13.760	13.781	13.802	13.823	13.844	13.864	13.885	13.906	13.927	13.948	13.969	<b>790</b>
<b>800</b>	13.969	13.989	14.010	14.031	14.052	14.073	14.094	14.114	14.135	14.156	14.177	<b>800</b>
<b>810</b>	14.177	14.198	14.219	14.240	14.260	14.281	14.302	14.323	14.344	14.365	14.386	<b>810</b>
<b>820</b>	14.386	14.407	14.428	14.448	14.469	14.490	14.511	14.532	14.553	14.574	14.595	<b>820</b>
<b>830</b>	14.595	14.616	14.637	14.658	14.679	14.700	14.721	14.742	14.763	14.784	14.804	<b>830</b>
<b>840</b>	14.804	14.825	14.846	14.867	14.888	14.909	14.930	14.951	14.972	14.993	15.014	<b>840</b>



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
<b>850</b>	15.014	15.035	15.056	15.077	15.098	15.119	15.140	15.162	15.183	15.204	15.225	<b>850</b>
<b>860</b>	15.225	15.246	15.267	15.288	15.309	15.330	15.351	15.372	15.393	15.414	15.435	<b>860</b>
<b>870</b>	15.435	15.456	15.477	15.498	15.520	15.541	15.562	15.583	15.604	15.625	15.646	<b>870</b>
<b>880</b>	15.646	15.667	15.688	15.709	15.731	15.752	15.773	15.794	15.815	15.836	15.857	<b>880</b>
<b>890</b>	15.857	15.878	15.900	15.921	15.942	15.963	15.984	16.005	16.027	16.048	16.069	<b>890</b>
<b>900</b>	16.069	16.090	16.111	16.132	16.154	16.175	16.196	16.217	16.238	16.260	16.281	<b>900</b>
<b>910</b>	16.281	16.302	16.323	16.344	16.366	16.387	16.408	16.429	16.450	16.472	16.493	<b>910</b>
<b>920</b>	16.493	16.514	16.535	16.557	16.578	16.599	16.620	16.642	16.663	16.684	16.705	<b>920</b>
<b>930</b>	16.705	16.727	16.748	16.769	16.790	16.812	16.833	16.854	16.875	16.897	16.918	<b>930</b>
<b>940</b>	16.918	16.939	16.961	16.982	17.003	17.025	17.046	17.067	17.088	17.110	17.131	<b>940</b>
<b>950</b>	17.131	17.152	17.174	17.195	17.216	17.238	17.259	17.280	17.302	17.323	17.344	<b>950</b>
<b>960</b>	17.344	17.366	17.387	17.408	17.430	17.451	17.472	17.494	17.515	17.536	17.558	<b>960</b>
<b>970</b>	17.558	17.579	17.601	17.622	17.643	17.665	17.686	17.707	17.729	17.750	17.772	<b>970</b>
<b>980</b>	17.772	17.793	17.814	17.836	17.857	17.879	17.900	17.921	17.943	17.964	17.986	<b>980</b>
<b>990</b>	17.986	18.007	18.028	18.050	18.071	18.093	18.114	18.136	18.157	18.178	18.200	<b>990</b>
<b>1000</b>	18.200	18.221	18.243	18.264	18.286	18.307	18.328	18.350	18.371	18.393	18.414	<b>1000</b>
<b>1010</b>	18.414	18.436	18.457	18.479	18.500	18.522	18.543	18.565	18.586	18.608	18.629	<b>1010</b>
<b>1020</b>	18.629	18.650	18.672	18.693	18.715	18.736	18.758	18.779	18.801	18.822	18.844	<b>1020</b>
<b>1030</b>	18.844	18.865	18.887	18.908	18.930	18.951	18.973	18.994	19.016	19.037	19.059	<b>1030</b>
<b>1040</b>	19.059	19.081	19.102	19.124	19.145	19.167	19.188	19.210	19.231	19.253	19.274	<b>1040</b>
<b>1050</b>	19.274	19.296	19.317	19.339	19.360	19.382	19.404	19.425	19.447	19.468	19.490	<b>1050</b>
<b>1060</b>	19.490	19.511	19.533	19.554	19.576	19.598	19.619	19.641	19.662	19.684	19.705	<b>1060</b>
<b>1070</b>	19.705	19.727	19.749	19.770	19.792	19.813	19.835	19.857	19.878	19.900	19.921	<b>1070</b>
<b>1080</b>	19.921	19.943	19.964	19.986	20.008	20.029	20.051	20.072	20.094	20.116	20.137	<b>1080</b>
<b>1090</b>	20.137	20.159	20.181	20.202	20.224	20.245	20.267	20.289	20.310	20.332	20.353	<b>1090</b>
<b>1100</b>	20.353	20.375	20.397	20.418	20.440	20.462	20.483	20.505	20.527	20.548	20.570	<b>1100</b>
<b>1110</b>	20.570	20.591	20.613	20.635	20.656	20.678	20.700	20.721	20.743	20.765	20.786	<b>1110</b>
<b>1120</b>	20.786	20.808	20.830	20.851	20.873	20.895	20.916	20.938	20.960	20.981	21.003	<b>1120</b>
<b>1130</b>	21.003	21.025	21.046	21.068	21.090	21.111	21.133	21.155	21.176	21.198	21.220	<b>1130</b>
<b>1140</b>	21.220	21.241	21.263	21.285	21.306	21.328	21.350	21.371	21.393	21.415	21.437	<b>1140</b>
<b>1150</b>	21.437	21.458	21.480	21.502	21.523	21.545	21.567	21.588	21.610	21.632	21.654	<b>1150</b>
<b>1160</b>	21.654	21.675	21.697	21.719	21.740	21.762	21.784	21.806	21.827	21.849	21.871	<b>1160</b>
<b>1170</b>	21.871	21.892	21.914	21.936	21.958	21.979	22.001	22.023	22.044	22.066	22.088	<b>1170</b>
<b>1180</b>	22.088	22.110	22.131	22.153	22.175	22.197	22.218	22.240	22.262	22.284	22.305	<b>1180</b>
<b>1190</b>	22.305	22.327	22.349	22.370	22.392	22.414	22.436	22.457	22.479	22.501	22.523	<b>1190</b>



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
<b>1200</b>	22.523	22.544	22.566	22.588	22.610	22.631	22.653	22.675	22.697	22.718	22.740	<b>1200</b>
<b>1210</b>	22.740	22.762	22.784	22.805	22.827	22.849	22.871	22.893	22.914	22.936	22.958	<b>1210</b>
<b>1220</b>	22.958	22.980	23.001	23.023	23.045	23.067	23.088	23.110	23.132	23.154	23.176	<b>1220</b>
<b>1230</b>	23.176	23.197	23.219	23.241	23.263	23.284	23.306	23.328	23.350	23.372	23.393	<b>1230</b>
<b>1240</b>	23.393	23.415	23.437	23.459	23.480	23.502	23.524	23.546	23.568	23.589	23.611	<b>1240</b>
<b>1250</b>	23.611	23.633	23.655	23.676	23.698	23.720	23.742	23.764	23.785	23.807	23.829	<b>1250</b>
<b>1260</b>	23.829	23.851	23.873	23.894	23.916	23.938	23.960	23.982	24.003	24.025	24.047	<b>1260</b>
<b>1270</b>	24.047	24.069	24.091	24.112	24.134	24.156	24.178	24.200	24.221	24.243	24.265	<b>1270</b>
<b>1280</b>	24.265	24.287	24.309	24.330	24.352	24.374	24.396	24.418	24.439	24.461	24.483	<b>1280</b>
<b>1290</b>	24.483	24.505	24.527	24.548	24.570	24.592	24.614	24.636	24.658	24.679	24.701	<b>1290</b>
<b>1300</b>	24.701	24.723	24.745	24.767	24.788	24.810	24.832	24.854	24.876	24.897	24.919	<b>1300</b>
<b>1310</b>	24.919	24.941	24.963	24.985	25.007	25.028	25.050	25.072	25.094	25.116	25.137	<b>1310</b>
<b>1320</b>	25.137	25.159	25.181	25.203	25.225	25.247	25.268	25.290	25.312	25.334	25.356	<b>1320</b>
<b>1330</b>	25.356	25.377	25.399	25.421	25.443	25.465	25.487	25.508	25.530	25.552	25.574	<b>1330</b>
<b>1340</b>	25.574	25.596	25.618	25.639	25.661	25.683	25.705	25.727	25.748	25.770	25.792	<b>1340</b>
<b>1350</b>	25.792	25.814	25.836	25.858	25.879	25.901	25.923	25.945	25.967	25.989	26.010	<b>1350</b>
<b>1360</b>	26.010	26.032	26.054	26.076	26.098	26.119	26.141	26.163	26.185	26.207	26.229	<b>1360</b>
<b>1370</b>	26.229	26.250	26.272	26.294	26.316	26.338	26.360	26.381	26.403	26.425	26.447	<b>1370</b>
<b>1380</b>	26.447	26.469	26.491	26.512	26.534	26.556	26.578	26.600	26.622	26.643	26.665	<b>1380</b>
<b>1390</b>	26.665	26.687	26.709	26.731	26.752	26.774	26.796	26.818	26.840	26.862	26.883	<b>1390</b>
<b>1400</b>	26.883	26.905	26.927	26.949	26.971	26.993	27.014	27.036	27.058	27.080	27.102	<b>1400</b>
<b>1410</b>	27.102	27.124	27.145	27.167	27.189	27.211	27.233	27.254	27.276	27.298	27.320	<b>1410</b>
<b>1420</b>	27.320	27.342	27.364	27.385	27.407	27.429	27.451	27.473	27.495	27.516	27.538	<b>1420</b>
<b>1430</b>	27.538	27.560	27.582	27.604	27.625	27.647	27.669	27.691	27.713	27.735	27.756	<b>1430</b>
<b>1440</b>	27.756	27.778	27.800	27.822	27.844	27.866	27.887	27.909	27.931	27.953	27.975	<b>1440</b>
<b>1450</b>	27.975	27.996	28.018	28.040	28.062	28.084	28.105	28.127	28.149	28.171	28.193	<b>1450</b>
<b>1460</b>	28.193	28.215	28.236	28.258	28.280	28.302	28.324	28.345	28.367	28.389	28.411	<b>1460</b>
<b>1470</b>	28.411	28.433	28.455	28.476	28.498	28.520	28.542	28.564	28.585	28.607	28.629	<b>1470</b>
<b>1480</b>	28.629	28.651	28.673	28.694	28.716	28.738	28.760	28.782	28.803	28.825	28.847	<b>1480</b>
<b>1490</b>	28.847	28.869	28.891	28.912	28.934	28.956	28.978	29.000	29.021	29.043	29.065	<b>1490</b>
<b>1500</b>	29.065	29.087	29.109	29.130	29.152	29.174	29.196	29.218	29.239	29.261	29.283	<b>1500</b>
<b>1510</b>	29.283	29.305	29.327	29.348	29.370	29.392	29.414	29.436	29.457	29.479	29.501	<b>1510</b>
<b>1520</b>	29.501	29.523	29.545	29.566	29.588	29.610	29.632	29.653	29.675	29.697	29.719	<b>1520</b>
<b>1530</b>	29.719	29.741	29.762	29.784	29.806	29.828	29.850	29.871	29.893	29.915	29.937	<b>1530</b>
<b>1540</b>	29.937	29.958	29.980	30.002	30.024	30.046	30.067	30.089	30.111	30.133	30.154	<b>1540</b>



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
<b>1550</b>	30.154	30.176	30.198	30.220	30.242	30.263	30.285	30.307	30.329	30.350	30.372	<b>1550</b>
<b>1560</b>	30.372	30.394	30.416	30.437	30.459	30.481	30.503	30.524	30.546	30.568	30.590	<b>1560</b>
<b>1570</b>	30.590	30.611	30.633	30.655	30.677	30.699	30.720	30.742	30.764	30.786	30.807	<b>1570</b>
<b>1580</b>	30.807	30.829	30.851	30.873	30.894	30.916	30.938	30.960	30.981	31.003	31.025	<b>1580</b>
<b>1590</b>	31.025	31.047	31.068	31.090	31.112	31.133	31.155	31.177	31.199	31.220	31.242	<b>1590</b>
<b>1600</b>	31.242	31.264	31.286	31.307	31.329	31.351	31.373	31.394	31.416	31.438	31.459	<b>1600</b>
<b>1610</b>	31.459	31.481	31.503	31.525	31.546	31.568	31.590	31.612	31.633	31.655	31.677	<b>1610</b>
<b>1620</b>	31.677	31.698	31.720	31.742	31.764	31.785	31.807	31.829	31.850	31.872	31.894	<b>1620</b>
<b>1630</b>	31.894	31.916	31.937	31.959	31.981	32.002	32.024	32.046	32.068	32.089	32.111	<b>1630</b>
<b>1640</b>	32.111	32.133	32.154	32.176	32.198	32.219	32.241	32.263	32.284	32.306	32.328	<b>1640</b>
<b>1650</b>	32.328	32.350	32.371	32.393	32.415	32.436	32.458	32.480	32.501	32.523	32.545	<b>1650</b>
<b>1660</b>	32.545	32.566	32.588	32.610	32.631	32.653	32.675	32.696	32.718	32.740	32.761	<b>1660</b>
<b>1670</b>	32.761	32.783	32.805	32.826	32.848	32.870	32.891	32.913	32.935	32.956	32.978	<b>1670</b>
<b>1680</b>	32.978	33.000	33.021	33.043	33.065	33.086	33.108	33.130	33.151	33.173	33.195	<b>1680</b>
<b>1690</b>	33.195	33.216	33.238	33.260	33.281	33.303	33.325	33.346	33.368	33.389	33.411	<b>1690</b>
<b>1700</b>	33.411	33.433	33.454	33.476	33.498	33.519	33.541	33.563	33.584	33.606	33.627	<b>1700</b>
<b>1710</b>	33.627	33.649	33.671	33.692	33.714	33.736	33.757	33.779	33.800	33.822	33.844	<b>1710</b>
<b>1720</b>	33.844	33.865	33.887	33.908	33.930	33.952	33.973	33.995	34.016	34.038	34.060	<b>1720</b>
<b>1730</b>	34.060	34.081	34.103	34.124	34.146	34.168	34.189	34.211	34.232	34.254	34.276	<b>1730</b>
<b>1740</b>	34.276	34.297	34.319	34.340	34.362	34.384	34.405	34.427	34.448	34.470	34.491	<b>1740</b>
<b>1750</b>	34.491	34.513	34.535	34.556	34.578	34.599	34.621	34.642	34.664	34.686	34.707	<b>1750</b>
<b>1760</b>	34.707	34.729	34.750	34.772	34.793	34.815	34.836	34.858	34.879	34.901	34.923	<b>1760</b>
<b>1770</b>	34.923	34.944	34.966	34.987	35.009	35.030	35.052	35.073	35.095	35.116	35.138	<b>1770</b>
<b>1780</b>	35.138	35.160	35.181	35.203	35.224	35.246	35.267	35.289	35.310	35.332	35.353	<b>1780</b>
<b>1790</b>	35.353	35.375	35.396	35.418	35.439	35.461	35.482	35.504	35.525	35.547	35.568	<b>1790</b>
<b>1800</b>	35.568	35.590	35.611	35.633	35.654	35.676	35.697	35.719	35.740	35.762	35.783	<b>1800</b>
<b>1810</b>	35.783	35.805	35.826	35.848	35.869	35.891	35.912	35.934	35.955	35.977	35.998	<b>1810</b>
<b>1820</b>	35.998	36.019	36.041	36.062	36.084	36.105	36.127	36.148	36.170	36.191	36.213	<b>1820</b>
<b>1830</b>	36.213	36.234	36.256	36.277	36.298	36.320	36.341	36.363	36.384	36.406	36.427	<b>1830</b>
<b>1840</b>	36.427	36.449	36.470	36.491	36.513	36.534	36.556	36.577	36.599	36.620	36.641	<b>1840</b>
<b>1850</b>	36.641	36.663	36.684	36.706	36.727	36.748	36.770	36.791	36.813	36.834	36.855	<b>1850</b>
<b>1860</b>	36.855	36.877	36.898	36.920	36.941	36.962	36.984	37.005	37.027	37.048	37.069	<b>1860</b>
<b>1870</b>	37.069	37.091	37.112	37.134	37.155	37.176	37.198	37.219	37.240	37.262	37.283	<b>1870</b>
<b>1880</b>	37.283	37.305	37.326	37.347	37.369	37.390	37.411	37.433	37.454	37.475	37.497	<b>1880</b>
<b>1890</b>	37.497	37.518	37.539	37.561	37.582	37.603	37.625	37.646	37.667	37.689	37.710	<b>1890</b>



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
1900	37.710	37.731	37.753	37.774	37.795	37.817	37.838	37.859	37.881	37.902	37.923	1900
1910	37.923	37.945	37.966	37.987	38.009	38.030	38.051	38.073	38.094	38.115	38.136	1910
1920	38.136	38.158	38.179	38.200	38.222	38.243	38.264	38.285	38.307	38.328	38.349	1920
1930	38.349	38.370	38.392	38.413	38.434	38.456	38.477	38.498	38.519	38.541	38.562	1930
1940	38.562	38.583	38.604	38.626	38.647	38.668	38.689	38.711	38.732	38.753	38.774	1940
1950	38.774	38.795	38.817	38.838	38.859	38.880	38.902	38.923	38.944	38.965	38.986	1950
1960	38.986	39.008	39.029	39.050	39.071	39.093	39.114	39.135	39.156	39.177	39.198	1960
1970	39.198	39.220	39.241	39.262	39.283	39.304	39.326	39.347	39.368	39.389	39.410	1970
1980	39.410	39.431	39.453	39.474	39.495	39.516	39.537	39.558	39.580	39.601	39.622	1980
1990	39.622	39.643	39.664	39.685	39.706	39.728	39.749	39.770	39.791	39.812	39.833	1990
2000	39.833	39.854	39.875	39.897	39.918	39.939	39.960	39.981	40.002	40.023	40.044	2000
2010	40.044	40.066	40.087	40.108	40.129	40.150	40.171	40.192	40.213	40.234	40.255	2010
2020	40.255	40.276	40.297	40.319	40.340	40.361	40.382	40.403	40.424	40.445	40.466	2020
2030	40.466	40.487	40.508	40.529	40.550	40.571	40.592	40.613	40.634	40.655	40.677	2030
2040	40.677	40.698	40.719	40.740	40.761	40.782	40.803	40.824	40.845	40.866	40.887	2040
2050	40.887	40.908	40.929	40.950	40.971	40.992	41.013	41.034	41.055	41.076	41.097	2050
2060	41.097	41.118	41.139	41.160	41.181	41.202	41.223	41.244	41.265	41.286	41.307	2060
2070	41.307	41.328	41.349	41.370	41.390	41.411	41.432	41.453	41.474	41.495	41.516	2070
2080	41.516	41.537	41.558	41.579	41.600	41.621	41.642	41.663	41.684	41.705	41.725	2080
2090	41.725	41.746	41.767	41.788	41.809	41.830	41.851	41.872	41.893	41.914	41.935	2090
2100	41.935	41.955	41.976	41.997	42.018	42.039	42.060	42.081	42.102	42.123	42.143	2100
2110	42.143	42.164	42.185	42.206	42.227	42.248	42.269	42.289	42.310	42.331	42.352	2110
2120	42.352	42.373	42.394	42.415	42.435	42.456	42.477	42.498	42.519	42.540	42.560	2120
2130	42.560	42.581	42.602	42.623	42.644	42.664	42.685	42.706	42.727	42.748	42.768	2130
2140	42.768	42.789	42.810	42.831	42.852	42.872	42.893	42.914	42.935	42.956	42.976	2140
2150	42.976	42.997	43.018	43.039	43.059	43.080	43.101	43.122	43.142	43.163	43.184	2150
2160	43.184	43.205	43.225	43.246	43.267	43.288	43.308	43.329	43.350	43.370	43.391	2160
2170	43.391	43.412	43.433	43.453	43.474	43.495	43.515	43.536	43.557	43.578	43.598	2170
2180	43.598	43.619	43.640	43.660	43.681	43.702	43.722	43.743	43.764	43.784	43.805	2180
2190	43.805	43.826	43.846	43.867	43.888	43.908	43.929	43.950	43.970	43.991	44.012	2190
2200	44.012	44.032	44.053	44.073	44.094	44.115	44.135	44.156	44.177	44.197	44.218	2200
2210	44.218	44.238	44.259	44.280	44.300	44.321	44.341	44.362	44.383	44.403	44.424	2210
2220	44.424	44.444	44.465	44.485	44.506	44.527	44.547	44.568	44.588	44.609	44.629	2220
2230	44.629	44.650	44.671	44.691	44.712	44.732	44.753	44.773	44.794	44.814	44.835	2230
2240	44.835	44.855	44.876	44.896	44.917	44.937	44.958	44.978	44.999	45.019	45.040	2240



## Type N Thermocouple Reference Tables (Fahrenheit)

### Thermoelectric Voltage in Millivolts

°F	0	1	2	3	4	5	6	7	8	9	10	°F
<b>2250</b>	45.040	45.060	45.081	45.101	45.122	45.142	45.163	45.183	45.204	45.224	45.245	<b>2250</b>
<b>2260</b>	45.245	45.265	45.286	45.306	45.326	45.347	45.367	45.388	45.408	45.429	45.449	<b>2260</b>
<b>2270</b>	45.449	45.469	45.490	45.510	45.531	45.551	45.572	45.592	45.612	45.633	45.653	<b>2270</b>
<b>2280</b>	45.653	45.674	45.694	45.714	45.735	45.755	45.775	45.796	45.816	45.837	45.857	<b>2280</b>
<b>2290</b>	45.857	45.877	45.898	45.918	45.938	45.959	45.979	45.999	46.020	46.040	46.060	<b>2290</b>
<b>*2300</b>	46.060	46.081	46.101	46.121	46.142	46.162	46.182	46.202	46.223	46.243	46.263	<b>2300</b>
<b>2310</b>	46.263	46.284	46.304	46.324	46.344	46.365	46.385	46.405	46.425	46.446	46.466	<b>2310</b>
<b>2320</b>	46.466	46.486	46.506	46.527	46.547	46.567	46.587	46.608	46.628	46.648	46.668	<b>2320</b>
<b>2330</b>	46.668	46.688	46.709	46.729	46.749	46.769	46.789	46.810	46.830	46.850	46.870	<b>2330</b>
<b>2340</b>	46.870	46.890	46.910	46.931	46.951	46.971	46.991	47.011	47.031	47.051	47.071	<b>2340</b>
<b>2350</b>	47.071	47.092	47.112	47.132	47.152	47.172	47.192	47.212	47.232	47.252	47.272	<b>2350</b>
<b>2360</b>	47.272	47.292	47.312	47.333	47.353	47.373	47.393	47.413	47.433	47.453	47.473	<b>2360</b>
<b>2370</b>	47.473	47.493	47.513									<b>2370</b>

\* Represents the maximum temperature up to which calibration tolerances have been established.

Reference N.I.S.T. Monograph 175 (ITS-90).  
Temperature in Degrees °F, reference junction at 32°F.